

LT LED track

RANGE	LT
REF.	LTLED-
TYPE	LED PROJECTOR
DIMENSIONS	195 x 57 mm
WEIGHT	0,353 Kg
MATERIAL	ALUMINIUM/BRASS
FINISH	BRASS/ALUMINIUM/WHITE/BLACK
VOLTAGE	120 - 250 V
FREQUENCY	50 / 60 Hz
FEEDER KIT	250 mA (INCLUDED)
DIMMABLE	NO
POWER	8,8 W
POWER FACTOR	0,90
SERVICE LIFE	50.000 h
CUT DIAMETER	MAX Ø 30 mm
IP RATING	IP44
LIGHTING DISTRIBUTION	DIRECT
COLOR TEMPERATURE	3000 K
CRI	90
MACADAM ELLIPSE	3
LIGHTING FLUX	1035 lm
LUMINOUS EFFICACY	118 lm/W
OPENING DEGREES	15° / 24°
TILTING VERTICAL AXIS	90°
ROTATION HORIZONTAL AXIS	350°



reference builder

TYPE	INSTALL	LIGHTING	POWER	C. TEMP	BEAM	CRI	FINISH	DIMING
	- (track)							
	T (trim)	COB (cob)	for LM 88 (8,8W)	30 (3000K)	15 (15°)	80 (CRI>80)	00L (white)	-
LTL (projector)	P (rosette)	LM (led module)	95 (9,5W)	40 (4000K)	24 (24°)	90 (CRI>90)	09L (black)	(on/off)
	Y (suspended)	GU10 (gu10 led lamp)	122 (12,2W) for COB		36 (36°)		02 (brass)	D (DALI)
	S (surface)							

Other color temperatures available under request

Order example:

LT COB T 7 122 30 24 00L D

LT projector cob trim 12,2W 3000k 24° CRI 80 white finish Dali

